


Current Equipment Type

TYPE 2D21
MINIATURE
HOT CATHODE
GAS FILLED
THYRATRON



RATINGS

Heater Voltage	6.3 volts
Heater Current	0.6 amp.
Cathode Heating Time	10 secs. min.
Peak Forward Anode Voltage	650 volts max.
Peak Inverse Voltage	1,300 volts max.
Peak Screen Grid Voltage before Conduction	-100 volts max.
†Average Screen Grid Voltage during Conduction	-10 volts max.
Peak Control Grid Voltage before Conduction	-100 volts max.
Peak Cathode Current	0.5 amp. max.
†Average Cathode Current	0.1 amp. max.
Surge Current (Duration 0.1 sec. max.)	10 amps. max.
†Average Screen Current	0.01 amp. max.
†Average Control Grid Current	0.01 amp. max.
Grid Circuit Resistance	10 MΩ max.
Peak Heater-Cathode Voltage, Heater Negative	100 volts max.
Peak Heater-Cathode Voltage, Heater Positive	25 volts max.
Ambient Temperature Range	-75°C. to 90°C.

† Averaged over any interval of 30 seconds.

OPERATING CHARACTERISTICS

Voltage Drop	8 volts approx.
Control Grid Control Ratio ($Rg_1 = 0\Omega$)	250 approx.
Screen Grid Control Ratio ($Rg_2 = 0\Omega$)	1,000 approx.

RELAY SERVICE

Anode Voltage	117	460	volts R.M.S.
Direct Screen Grid Voltage	0	0	0	volts
Control Grid Voltage (180° out of phase with Va)	5	—	—	volts R.M.S.
Direct Control Grid Voltage	—	—	—	volts
Control Grid Signal Voltage	5	6	—	volts peak
Control Grid Circuit Resistance	1.0	1.0	—	MΩ
*Anode Circuit Resistance	1.2	2.0	—	kΩ

* Anode circuit resistance, including the valve load, must be sufficient to prevent the cathode current from exceeding the valve ratings.

INTER-ELECTRODE CAPACITANCES

Grid to Anode Input	0.026 pF	Output	1.6 pF
	2.4 pF				

Type 2D21 is a commercial equivalent to the CV797.

